

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
29 January 2004 (29.01.2004)

PCT

(10) International Publication Number
WO 2004/009292 A1

(51) International Patent Classification⁷: B24C 3/00. 5/00, 7/00

(74) Agent: ZEMLYANITSIN, Mikhail Aleksandrovich; Nits "Eldis" Ran, Starosadsky per., 8-1a, Moscow, 101000 (RU).

(21) International Application Number:

PCT/RU2003/000358

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GII, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, SD, SE, SG, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(22) International Filing Date: 23 July 2003 (23.07.2003)

(84) Designated States (regional): ARIPO patent (GII, GM, KE, LS, MW, MV, SD, SI, SZ, TZ, UG, YM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IIE, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CR, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English

Published:
— with international search report

(26) Publication Language: English

(30) Priority Data:

2002119454 23 July 2002 (23.07.2002) RU

2002119455 23 July 2002 (23.07.2002) RU


(71) Applicant and

(72) Inventor: GRECHISHKIN, Oleg Ivanovich [RU/RU]; ZIISK, der. Sofyino, 18, Naro-Fominsky raion. Moskovskaya obl., 143395 (RU).

{Continued on next page}

(54) Title: ABRASIVE BLASTING DEVICE

WO 2004/009292 A1



(57) Abstract: The device provides for both "cold" and "hot" processing. It comprises a nozzle gun, an abrasive vessel, a batcher, an ejection-type mixer, a fuel tank, a receiver. The nozzle gun comprises a combustion chamber (108), a tubular element (114) for air/abrasive mixture feeding, a nozzle (128), swirlers of the fuel blend (122) and of gaseous oxidant (124). The combustion chamber (108) at its perforated wall area (110) is embodied with variable cross-section. The batcher comprises a means for independent regulation of the seat position with respect to the position of the slide-valve rod, a means for abrasive loosening and blow purging.